



120 VAC

- NOTES
1. RESISTORS ARE DESIGNATED IN OHMS, 10% & 1/2W UNLESS OTHERWISE SPECIFIED
 2. CAPACITORS ARE DESIGNATED IN MFD UNLESS OTHERWISE SPECIFIED
 3. C301 SUPPLIED AS PART OF 1403 & HAS A VALUE OF 5/660 VAC
 4. Ⓢ SCREWDRIVER ADJUSTMENT FRONT PANEL
 5. Ⓢ SCREWDRIVER ADJUSTMENT BENEATH FRONT PANEL
 6. Ⓢ RNOB ADJUSTMENT FRONT PANEL
 7. ALL SWITCHES SHOWN IN CCB POSITION EXCEPT S301.
 8. VOLTAGES MEASURED WITH SIMPSON 2000A VOLT/DC & 3000A VOLT/AC METER WITH RESPECT TO GROUND UNLESS OTHERWISE SPECIFIED.

- S101 & S201 METER SELECTOR
 POS 1 BALANCE
 2 ZERO
 3 BALANCE
- S102 & S202 TIME CONSTANT
 POS 1-6
- S301 MATRIXING
 POS 1 LEFT & RIGHT
 2 LATERAL & VERTICAL
- R318 RES B+ ADJ.
- AT101 & AT201 INPUT BATH
 R105 & R205 BALANCE
 R115 & R215 AC THRESHOLD
 R117 & R217 DC THRESHOLD
 R142 & R242 ZERO

670 DL
 SC